



# Desmoldex F

## Desmoldante lubricante antiadherente



### Características

- » Resistente altas y bajas temperaturas
  - » Desmoldante, lubricante y antiadherente
  - » Producto fabricado a base de polisilaxano
- Lubrica líneas de proceso, reduce la fricción en superficies evitando que los objetos se adhieran, inodoro e incoloro, no deja manchas, no oscurece, soporta temperaturas desde 4.4 C° hasta 260°.

### Instrucciones

- Limpie la superficie
- Agite antes de usar
- Mantenga el bote en posición vertical
- Aplique a una distancia de 30 cm
- Una sola aplicación es suficiente

### Para uso en:

- Industria Farmacéutica
- Industria del Pañal
- Industria del Dulce
- Industria del Plástico
- Industria Textil
- Industria Electrónica



- |               |              |              |             |
|---------------|--------------|--------------|-------------|
| • Fuego       | 4 Extremo    | • Fire       | 4 Very High |
| • Reactividad | 3 Alto       | • Reactivity | 3 High      |
| • Especial    | 2 Moderado   | • Special    | 2 Moderate  |
| • Salud       | 1 Ligero     | • Health     | 1 Low       |
|               | 0 Sin riesgo |              | 0 No risk   |

### Presentación



454 ml

### Precauciones

- No lo exponga a temperaturas mayores de 50°
- Contenido bajo presión
- No lo perforo ni incinere
- No se ingiera
- No se deje al alcance de los niños



# Desmoldex F

Release agent, lubricant and nonstick

## Characteristics

- » Resistant to high and low temperatures
  - » Release agent, lubricant and nonstick
  - » Product made of polysiloxane
- Lubricates process lines, reduces friction surfaces preventing sticking objects, odorless and colorless, non-staining, not draining, withstands temperatures from 4.4°C (39.92°F) to 260°C (500°F).

## Usage instructions

Clean the surface  
Shake before using  
Keep the bottle upright  
Apply at 11.80 inches  
A single shot is enough


### For use in:

Pharmaceuticals industry  
Diaper industry  
Confectionery industry  
Plastics industry  
Textile industry  
Electronic industry



- |               |              |              |             |
|---------------|--------------|--------------|-------------|
| • Fuego       | 4 Extremo    | • Fire       | 4 Very High |
| • Reactividad | 3 Alto       | • Reactivity | 3 High      |
| • Especial    | 2 Moderado   | • Speical    | 2 Moderate  |
| • Salud       | 1 Ligerio    | • Health     | 1 Low       |
|               | 0 Sin riesgo |              | 0 No risk   |

## Presentación



16 oz.

## Advertencia

Do not expose to temperatures above 50°C/122° F  
Content under pressure  
Do not puncture or incinerate  
Do not ingest  
keep out of reach of children